

CEM -DT-172/172TK Temperature and Humidity Datalogger

	172	172TK
Temp range	-40 to 70°C -40 to 158°F	-40 to 70°C -40 to 158°F
Temp Accuracy	±1°C	±0.5°C
Humidity range	0 to 100%RH	0 to 100%RH
Humidity Accuracy	±2%RH	±2%RH
Temp K range		-200 to 1370°C(-328 to 2498°F)
Temp k Accuracy		Above -100°C(-148°F):0.15%rgd+1.0°C (1.8°F) Blow -100°C(-148°F):0.5%rgd+2.0°C (3.6°F)
Memory	32000(16000 each for temperature and humidity)	
Measuring rate	1sec.to 24h	
Battery life	Typically 3 years	
Analysis software	Windows 98/2000/XP/Vista/7	

DT-172/172TK Temperature and Humidity Datalogger



Model 172






Specifications	172	172TK
Temp range	-40 to 70°C -40 to 158°F	-40 to 70°C -40 to 158°F
Temp Accuracy	±1°C	±0.5°C
Humidity range	0 to 100%RH	0 to 100%RH
Humidity Accuracy	±2%RH	±2%RH
Temp K range		-200 to 1370°C(-328 to 2498°F)
Temp K Accuracy		Above -100°C (-148°F): 0.15%rgd+1.0°C(1.8°F) Blow -100°C (-148°F): 0.5%rgd+2.0°C(3.6°F)
Memory	32000(16000 each for temperature and humidity)	
Measuring rate	1sec. to 24h	
Battery life	typically 3 years	
Analysis software	windows 98/2000/XP/Vista/7	

Accessories :
3.6V Lithium battery, K-Temp probe(172TK), software and clamshell.
Size(HxWxD):34mm x 50mm x 32mm
Weight: 91g