


Kyoritsu Digital Clamp Meters

MODEL **2006**

- Pocket size, handy clamp meter.
- UL listed fire retardant plastic housing case.
- Multifunction instrument having voltage and resistance measurement functions in addition to all the ranges incorporated.



AC A	2/20/200A ±2%rdg±5dgt [50Hz~1kHz] (2/20A) ±2%rdg±5dgt [50/60Hz] (200A) ±3%rdg±10dgt [40Hz~1kHz] (200A)
AC V	2/20/200/500V ±1.5%rdg±2dgt [50/60Hz] ±1.5%rdg±5dgt [40Hz~1kHz]
DC V	2/20/200/500V ±1%rdg±2dgt
Ω	2kΩ ±1.5%rdg±2dgt
Continuity buzzer	buzzer sounds below 300~400Ω
Conductor Size	Ø19mm max.
Frequency Response	40Hz~1kHz
Withstand Voltage	2200V AC for 1 minute
Power Source	R6P (AA) (1.5V) × 2
Dimensions	184(L) × 54(W) × 32(D)mm
Weight	160g approx.
Accessories	7066 (Test Leads) 9066 (Carrying Case) R6P (AA) × 2 Instruction Manual
Optional	8004/8008 (Multi-Tran)