

- Display :** ● 3¹/₂ digits LCD with maximum reading 2000. ● Overload indication : "OL"
- Functions :** ● According to JISC1609 : 1993 and CNS 5119 general A class specifications.
- Spectral response close to CIE luminous spectral efficiency.
 - Measuring intensities of illumination in unit of Lux or Foot-candle.
 - Silicon photo diode and filter.
 - Cosine angular corrected.
 - Real Zero function.
 - Measuring all visible light sources.
 - USB interface, 7000 Records data logger(TM-203).

TM-203 Datalogging Light Meter

Specifications :

- Data hold.
- AVG func.
- Max / Min hold.
- Zero adjustment.
- Auto ranging.
- Auto power off .
- Datalogger.
- Sensor : Silicon photo diode and filter.
- Meter size : 172x56x38mm. (LxWxH)
- Weight : 250g. (including battery)



Protection Holster (optional accessory)

Measuring range	20, 200, 2000, 20000, 200000 Lux 20, 200, 2000, 20000 Foot-candle										
Accuracy	±3% (Calibrated to standard incandescent lamp 2856°K) ±6% (other visible light source)										
Angle deviation from cosine characteristics	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;">10°</td> <td style="width: 50%; border: none;">± 0.5%</td> </tr> <tr> <td style="border: none;">30°</td> <td style="border: none;">± 2%</td> </tr> <tr> <td style="border: none;">50°</td> <td style="border: none;">± 3%</td> </tr> <tr> <td style="border: none;">60°</td> <td style="border: none;">± 6%</td> </tr> <tr> <td style="border: none;">80°</td> <td style="border: none;">± 25%</td> </tr> </table>	10°	± 0.5%	30°	± 2%	50°	± 3%	60°	± 6%	80°	± 25%
10°	± 0.5%										
30°	± 2%										
50°	± 3%										
60°	± 6%										
80°	± 25%										

TM-204 Light Meter TM-205 Light Meter (Auto-Ranging)

Specifications :

- Data hold.
- Zero adjustment.
- Auto power off.
- Meter size : 172x56x38mm. (LxWxH)
- Weight : 250g. (including battery)
- MAX / MIN .
- Auto ranging.
- Sensor : Silicon photo diode and filter.

TM-204

TM-205



Measuring range	TM-204	200, 2000, 20000, 200000 Lux 20, 200, 2000, 20000 Foot-candle									
	TM-205	20, 200, 2000, 20000, 200000 Lux 20, 200, 2000, 20000 Foot-candle									
Accuracy	TM-204	±3% (Calibrated to standard incandescent lamp 2856°K) ±8% (other visible light source)									
	TM-205	±3% (Calibrated to standard incandescent lamp 2856°K) ±6% (other visible light source)									
Angle deviation from cosine characteristics	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;">10°</td> <td style="width: 50%; border: none;">±0.5%</td> </tr> <tr> <td style="border: none;">30°</td> <td style="border: none;">±2%</td> </tr> <tr> <td style="border: none;">50°</td> <td style="border: none;">±3%</td> </tr> <tr> <td style="border: none;">60°</td> <td style="border: none;">±6%</td> </tr> <tr> <td style="border: none;">80°</td> <td style="border: none;">±25%</td> </tr> </table>	10°	±0.5%	30°	±2%	50°	±3%	60°	±6%	80°	±25%
10°	±0.5%										
30°	±2%										
50°	±3%										
60°	±6%										
80°	±25%										