MICRO WAVE LEAKAGE DETECTOR

Model: EMF-810 ISO-9001, CE, IEC1010



勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787 Http://www. 100y. com. tw







The Art of Measurement

MICRO WAVE LEAKAGE DETECTOR

Model: EMF-810

FEATURES

- * This meter is specially designed for measuring or monitoring electromagnetic field value for the micro-wave frequency precisely.
- * Useful equipment to detect the leakage of micro wave oven.
- * Build in alarm setting, when the measuring value > 1 mW/cm^2, the buzzer will sound to remind that the measured device's micro wave EMF value (leakage value) is larger than the safety level.
- * The meter have been calibrated precisely on the frequency value 2.45 GHz.
- * Peak hold function to latch the max. measuring value.
- * Powered by 006P 9V battery and DC 9V adapter.
- * Except to measure the micro wave's EMF value, the detector also can measure the radio EMF value of hospital equipment, radar, radiation work, TV antenna, Radio station, welding equipment, baking- equipment, television, computer, factory, laboratory, and other environment...etc for reference.

	SPECIFICATIONS	STANKE TO COLUMN TO THE STANKEN	
Display	LCD size: 40 mm x 25 mm.		
WWW.100Y.C	Digit size: 12 mm x 6 mm.		
Measurement Unit	mW/cm^2	M.TW WWW.100X.COM.	
Operating Frequency Range	2.45 GHz ± 50 MHz * Beyond the 2.45 GHz ± 50 MHz, other frequency's EMF value between 30 MHz to 3 GHz also can be measured, but for reference only.		
Measurement Range	0 to 1.999 mW/cm^2	OY.COM.TW WWW.100TC	
Accuracy	Accuracy tested under 2.45 GHz ± 50 MHz and * measurement level is 0.1 mW/cm^2.		
Peak Hold	To latch the max. measuring value.		
Alarm Setting	If reading value > 1 mW/cm^2 approximately, the buzzer will sound.		
Sensor Space Length	50 mm.		
Over Indicator	Display shows " OL ".	勝 特 力 材 料 886-3-5753170	
Power Current	Approx. DC 1.86 mA.	胜特力电子(上海) 86-21-34970699	
Weight	202 g/ 0.445 LB.	胜特力电子(深圳) 86-755-8329878	
Dimension	152 x 69 x 36.3 mm. (6.0 x 2.7 x 1.4 inch).		
Standard	Operation Manual 1 PC.		
Accessory			
Optional	Soft carrying case, CA-52A.		
Accessory			

^{*} Appearance and specifications listed in this brochure are subject to change without notice.