

Features

- Single Output DC Power Supply
- 60 V/ 3A Adjustable Output
- 5V/ 1A fixed output
- 12V/ 1A fixed output
- Two Digital Panel Meters
- 3 1/2 digits LED display
- Constant Voltage
- Constant Current operation
- High Efficiency
- Light and Compact Design
- High Power Density
- Overload Protection
- Reverse Polarity Protection



MP-6003

SPECIFICATIONS

Constant Voltage Operation

Range	0 ~ 60 V
Line regulation	CV ≤ 0.01%+2mV
Load regulation	CV ≤ 0.01%+2mV
Ripple & Noise	CV ≤ 1mV(RMS)
Temperature coefficient	≤ 150ppm

Constant Current Operation

Range	0 ~ 3 A
Line regulation	CC ≤ 0.2%+2mA
Load regulation	CC ≤ 0.2%+5mA
Temperature coefficient	≤ 150ppm

Fixed 5V/1A Output

Voltage accuracy	±1%
Ripple & Noise	CV ≤ 2mV(RMS)

Fixed 12V/1A Output

Voltage accuracy	±1%
Ripple & Noise	CV ≤ 2mV(RMS)

Display accuracy

3 1/2 digits LED	≤ 0.1%+1d
Recover time	±100μS

Weight and Dimension

Weight (kg)	5.6
Dimension L×W×H	335x130x165mm

Main Power Supply

220V±10%, 50/60Hz±2Hz