

Inrush current (366)

True RMS (363/366)



The 360 series clamp meters offer all needed features for measurement. It with small bodies and jaws design for perfectly handhold and tight place testing. A large backlit display (on most models) is easy to see and a handy Display Hold keeps measurements on the display. Measuring starting current for motors, lighting, etc. is easy with the inrush current function (366 only).

- Double molded plastic housing
- Inrush current function (366 only)
- Auto Power Off

Features	360	361	362	363	366
Current measurement	AC	AC	AC/DC	AC/DC	AC/DC
Max. Resolution	1mA	1mA	10mA	10mA	10mA
LCD display counts	2000	4000	4000	4000	6000
AC True RMS	*	*	*	*	*
Display with backlight	*	*	*	*	*
Data Hold	*	*	*	*	*
Max Hold	*	*	*	*	*
Zero Function	*	*	*	*	*
Auto Power Off	*	*	*	*	*
Low battery indication	*	*	*	*	*
Peak Current	*	*	*	*	*
Inrush Current	*	*	*	*	*
1.2" (30mm) Jaw opening	*	*	*	*	*

Specifications	Max Range	Basic Accuracy	360	361	362	363	366
Voltage DC	600V	±(0.5%+1d)	*	*	*	*	*
Voltage AC	600V	±(1.5%+2d)	*	*	*	*	*
Current DC	400A	±(2.0%+5d)	*	*	*	*	600A
Current AC	400A	±(2.5%+4d)	*	*	*	*	*
Resistance	40MΩ	±(3.0%+5d)	20MΩ	*	*	*	60MΩ
Temperature	1000°C/ 1832°F	±(3.0%+3d)	*	*	*	*	*
Capacitance	100uF	±(2.5%+5d)	*	*	*	40mF	60mF
Frequency	10MHz	±(1.2%+2d)	*	*	*	*	*
Inrush Current	600A	±(1.5%+2d)	*	*	*	*	*
Continuity check	Buzzer sounds at 50Ω	*	*	*	*	*	*
Diode test	Test current 0.3mA	*	*	*	*	*	*

Size(HxWxD): 197mm x 70mm x 40mm

Weight: 183g

Accessories:

Test leads, gift box with carrying case, Temperature probe(361,362, 363, 366 only) and 9V battery.



Model 360



EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031



Model 362



Model 363



370 clamp meter offers all needed features for measurement. It has small bodies and jaws design for perfectly handhold and tight place testing. A large backlit display (on most models) is easy to see and a handy Display Hold keeps measurements on the display. Measuring starting current for motors, lighting, etc.



Heavy Duty housing design
Drop-proof to 2M

Features

200A AC Current measurement
4000 counts LCD display
Compact size
REL Function
Data Hold
Low battery indication
1.2" (30mm) Jaw opening

Specifications

Function	Max Range	Basic Accuracy
Voltage DC	600V	±(0.5%+1d)
Voltage AC	600V	±(0.5%+2d)
Current AC	200A	±(2.5%+4d)
Resistance	40MΩ	±(3.0%+5d)
Temperature	1000°C/ 1832°F	±(3.0%+3d)
Capacitance	100uF	±(2.5%+5d)
Frequency	10MHz	±(1.2%+2d)
Continuity check	Buzzer sounds at 50Ω	
Diode test	Test current 0.3mA	

Size(HxWxD): 230mm x 82mm x 40mm

Weight: 230g

Accessories:

Test leads, gift box with carrying case, Temperature probe and Two"AAA"1.5V batteries.

DT-380/381/382/383 Compact AC, AC/DC Autoranging Clamp Meters

The 380 series clamp meters offer all the features you need to fit the way you work. The small bodies and jaws fit perfectly in your hand and into tight places.

Features

Features	380	381	382	383
Current measurement	AC	AC	AC/DC	AC/DC
LCD display counts	2000	4000	2000	4000
Data Hold	*	*	*	*
REL (Zero) Function	*	*	*	*
Auto Power Off	*	*	*	*
Low battery indication	*	*	*	*
1.2" (30mm) Jaw opening	*	*	*	*
NCV Detection	*	*	*	*

Specifications

Function	Max Range	Basic Accuracy	380	381	382	383
Voltage DC	600V	±(0.5%+1d)	*	*	*	*
Voltage AC	600V	±(1.5%+2d)	*	*	*	*
Current DC	400A	±(2.0%+5d)	*	*	200A	*
Current AC	400A	±(2.5%+4d)	*	*	200A	*
Resistance	40MΩ	±(3.0%+5d)	20MΩ	*	20MΩ	*
Temperature	1000°C/ 1832°F	±(3.0%+3d)	*	*	*	*
Capacitance	100uF	±(2.5%+5d)	*	*	*	*
Frequency	10MHz	±(1.2%+2d)		10kHz		10kHz
Continuity check	Buzzer sounds at 50Ω					
Diode test	Test current 0.3mA					

Size(HxWxD): 230mm x 82mm x 40mm

Weight: 230g

Accessories:

Test leads, gift box with carrying case, Temperature probe and Two"AAA"1.5V batteries.



EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031



Model 370



EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031



Model 383