

Professional InfraRed Video Thermometers with TFT color LCD display & Imager Video format




Meterbox
Meterbox
Cloud Server



Worldwide Patent:
PCT/CN2010/000230
200910189276.8
200920261924.1

EMC
EN: 61326
EN: 60825-1



Dual laser targeting & D:S = 75:1 | JPG images / 3GP videos & Audio Recording | High accuracy (1.0%) measurement | Fold reading on the images

Applications

- Plant/General Maintenance
- HVAC/R
- Transportation/Automotive
- Cooling and Reheating
- Serving areas
- Food service Equipment



2.2" TFT color LCD display



Support **Images**(JPEG) capture capabilities



Support **Video**(3GP) capture capabilities



Support **IR, K-Type, Air, Dewpoint, Wet bulb Temp. & Air Humidity** measurement

Dual laser targeting

Date/Time setup controls

USB interface

Data Logger

Support **MicroSD** memory card extension



9860/9861/9862/9863/9865 Series Professional Infrared Video Thermometers with 2.2" color TFT LCD display & a microSD memory card for capturing images(JPEG) or video(3GP) for viewing on your PC, providing fast, easy and accurate readings for most surface temperature measurements. The measurement of dewpoint will be very visible for wet and dry proof. These series products are with international patent and good hands for industrial measurements and data analyzing. The user can be back in office to analyze the measured Infrared temperature readings under the support of software.

- High 75 to 1/50 to 1 distance to target ratio measures smaller surface areas at greater distances
- IR temperature measurement
- Air temperature and type K probe temperature measurement
- Relative humidity measurement
- Wet bulb temperature & dewpoint temperature measurement
- Unique flat surface, modern housing design

Features

	9860/9860S	9861/9861S	9862/9862S	9863	9865
2.2" TFT 320x240 pixels Color LCD display	*	*	*	*	*
Camera pixels	640x480	640x480	640x480	3.0 Mega	3.0 Mega
Images(JPEG) & Video(3GP)	*	*	*	*	*
MicroSD memory card & datalogger function	*	*	*	*	*
Dual laser targeting	*	*	*	*	*
Date/time setup controls	*	*	*	*	*
Auto Power Off	*	*	*	*	*
High Temperature	*	*	*	*	*
Max, Min, DIF, AVG record	*	*	*	*	*
High and low alarm	*	*	*	*	*
Adjustable emissivity & Trigger lock	*	*	*	*	*
Type K input	*	*	*	*	*
USB/ bluetooth interface	USB	USB	USB	USB/ Bluetooth	USB/ Bluetooth
Readings memories	*	*	*	*	*
Humidity & Air Temperature	*	*	*	*	*
Dewpoint & Wet bulb temperature	*	*	*	*	*
Audio Recording	*	*	*	*	*
Language selection	English, Chinese, French, German, Spanish				

Specifications

	9860/9860S	9861/9861S	9862/9862S	9863	9865
IR Temp. Range	-50°C to 1000°C -58°F to 1832°F	-50°C to 1600°C -58°F to 2912°F	-50°C to 2200°C -58°F to 3992°F	-50°C to 1000°C -58°F to 1832°F	-50°C to 2300°C -58°F to 4172°F
Response Time	Less than 300ms; Less than 150ms(9860S/9861S/9862S)			Less than 150ms	
Resolution	0.1" up 1000", 1" over 1000"				
Basic Accuracy (IR)	±1.0% of reading				
Optical Resolution	50:1 Distance to Spot size				75:1 Distance to Spot size
Emissivity Adjustable	0.10-1.0 Adjustable				
Type K Temp. Range	-50°C to 1370°C / -58°F to 2498°F				
Basic Accuracy (TK)	±0.5% of reading ±1°C				
Micro SD memory card	MAX. support 8GB				
Air Temp Range	0 to 50°C/32 to 122°F				
Air Temp Basic Accuracy	±0.5°C/1°F				
Humidity Range	0 to 100%RH				
Humidity Basic Accuracy	±2.5%RH(20%-80%RH)				
Dew Point Temp. Range	0 to 50°C/32 to 122°F				
Wet Bulb Temp. Range	0 to 50°C/32 to 122°F				



Size(HxWxD): 125mm x 58mm x 205mm
Weight: 494g
Accessories:
3.7V Li battery, Type K Temp. probe, USB cable, Carrying case and Gift box



Temperature probe
(Optional: NR-31B / TP-500 / TCP-100)

Worldwide Patent:
PCT/CN2010/000230
200910189276.8
200920261924.1

2.2" TFT Color LCD display

Capturing images(JPEG)
75 : 1 distance to spot size



Model 9863