

## DT-9915/9915T/9916/9917/9917T/9918/9918T Professional Digital Multimeters



IP67 dust and water proof

True RMS (9915T/9917T/9918T)



Model 9918



Model 9917



Model 9915

The seven models of the new 9915,9915T, 9916, 9917,9917T, 9918 and 9918T series are the new 4000 counts multimeters. They set the standard with a combination of precision, features, easy-to-use, safety and reliability.

9915T/9917T/9918T have True RMS AC Voltage, Current readings, as well as Frequency and Capacitance ranges.

### Safety Conformance

- EN61010-1 CAT IV 600V, CAT III 1000V
- 1000V input protection on all ranges
- 10A/1000V & 0.5A/1000V fuses protection on current ranges



EMC & LVD  
EN: 61326  
EN: 61010-1  
EN: 61010-02-031



Features	9915/9915T	9916	9917/9917T	9918/9918T
Digital display counts	4000	4000	4000	4000
True RMS measurement	9915T		9917T	9918T
Safety design	*	*	*	*
Relative zero	*	*	*	*
Data Hold	*	*	*	*
MAX/MIN recording mode				*
Auto Power Off	*	*	*	*
Peak capture mode				*
Wide capacitance range		20mF		*
Current DC/AC 40μA		*		*
Analog bargraph/segment				*

Specifications	Function	Max. Range	Basic Accuracy	9915/9915T	9916	9917/9917T	9918/9918T
Voltage DC	1000 V	±0.5%	*	*	*	*	
Voltage AC	1000V	±0.8%	*	*	*	*	
Current DC	10A	±1.2%	*	*	*	*	
Current AC	10A	±1.8%	*	*	*	*	
Resistance	40MΩ	±0.8%	*	*	*	*	
Duty Cycle	99.9%	±1.2%	*	*	*	*	
Frequency	10MHz	±1.5%	*	*	*	*	
Capacitance	200μF/40mF	±3.0%	200μF	20mF	200μF	40mF	
Temperature	760°C/1400°F	±3.0%	*	*	*	*	
Diode Check			*	*	*	*	
Continuity Test			*	*	*	*	

Size(HxWxD): 182mm x 82mm x 55mm  
Weight: 360g

Accessories:  
Test leads and 9V battery,  
Type K temperature probe (9917/9918/9917T/9918T), gift box with carrying case.

## DT-9926/9927/9927T/9928/9928T/9938 Professional Digital Multimeters



The three models of 9926, 9927 & 9927T series are the new 6000 counts multimeters. They are a combination of precision, features, easy-to-use, safety and reliability.

9928/9928T series are the new 11,000 counts and 9938 is the new 22,000 counts multimeter. They are a combination of precision, features, easy-to-use, safety and reliability.

9927T/9928T has True RMS AC Voltage and Current readings, MAX-MIN recording,

### Safety Conformance

- EN61010-1 CAT IV 600V, CAT III 1000V
- 1000V input protection on all ranges
- 10A/1000V & 0.5A/1000V fuses protection on current ranges



EMC & LVD  
EN: 61326  
EN: 61010-1  
EN: 61010-02-031



Features	9926	9927	9927T	9928	9928T	9938
Digital display counts	6000	6000	6000	11,000	11,000	22,000
Max.Resolution	0.1mV/0.1μA/0.1Ω			0.0 mV/0.01μA/0.01Ω		
True RMS measurement		*	*	*	*	*
Analog bargraph/segment	*/61	*/61	*/61	*	*	*
Safety design	*	*	*	*	*	*
Relative mode	*	*	*	*	*	*
Data Hold	*	*	*	*	*	*
MAX/MIN recording mode	*	*	*	*	*	*
Auto Ranging	*	*	*	*	*	*
Auto Power Off	*	*	*	*	*	*
Wide capacitance range	1000μF	1000μF	1000μF	110mF	110mF	*
Temperature function		*	*	*	*	*

Specifications	Function	Max. Range	Basic Accuracy
Voltage DC	1000 V	±0.09%	
Voltage AC	1000V	±0.8%	
Current DC	10A	±1.0%	
Current AC	10A	±1.5%	
Resistance	40MΩ	±0.3%	
Duty Cycle	99.9%	±1.2%	
Frequency	10MHz	±0.1%	
Capacitance	40mF	±3.5%	
Temperature	760°C/1400°F(9919)	±3.0%	
Diode Check			
Continuity Test			

Size(HxWxD): 182mm x 82mm x 55mm  
Weight: 360g

Accessories:  
Test leads, 9V battery,  
Type K temperature probe and gift box with carrying case.



Model 9927/9927T



Model 9926



Model 9928/9928T



Model 9938

