

St



123/125/125B/127 are used to measure the moisture level in sawn timber (also cardboard, paper) and hardened materials (plaster, concrete and mortar). They display the moisture level. The instruments have an average adjustment for European wood based on a wood temperature of 20°C.

127 is 2 in 1 digital and analog moisture meter



Model 125



Model 125B

Features

- Large LCD display
- Readings with Moisture Probe or Hammer Electrode
- Readings with Integral electro Pin

Specifications

| | |
|-----------------------|---------------------------|
| Measuring principle | Electrical resistance |
| Electrode length | 8mm |
| Electrodes | Integrated, replaceable |
| Measuring range | Wood: 6-44% |
| | Material: 0.2-2.0% |
| Display Accuracy | Wood: ±1% |
| | Material: ±0.05% (127) |
| Battery | 3 x Cr 2032, replaceables |
| Temperature measuring | 0-60°C |
| Ambient temperature | 0-40°C |
| Ambient moisture | 0-85% |

Size(HxWxD): 123/127: 130mm x 40mm x 33mm

Weight: 99g

Size(HxWxD): 125/125B: 140mm x 48mm x 33mm

Weight: 93g



Calibration and battery check



EMC
EN: 61326



replaceable pin



Accessories :
battery, clamshell

Model 123

