

ST-128M/128C

Pinless Moisture Meter

St

Sound Level Meters

Features

- Quickly indicate the moisture content of materials
- CM % measured function
- Depth of penetration about 20-40mm with alarms.
- Measure and HOLD Function
- MAX/MIN display Function
- Programmable moisture and humidity alarms (128C)
- Capacitive sensor type (128C)
- Auto Power Off & low battery indication
- White Backlit LCD Display

Specifications

Measuring Range	0.0~100.0 %
Penetration Depth	20~40mm
Resolution	0.1
Battery	Three "AAA" Batteries

Model 128M



EMC
EN: 61326



Button on both sides of the rugged housing, easy to use

Moisture Table of Comparison

Construction material	Display	Moisture status
Gypsum	<30 digits	dry
	30 - 60 digits	at risk
	>60 digits	wet
Cement	<25 digits	dry
	25 - 50 digits	at risk
	50 - 75 digits	wet
	>75 digits	all wet

Size(HxWxD): 242mm x 63mm x 30mm

Weight: 226g

Accessories:

3x"AAA" V battery, gift box with carrying case.



ST-126 3 in1 Non-Contact Moisture Meter with Laser Level & AC Voltage Finder

Specifications

Sensor Type	Non-Penetrating
Moisture % of H ₂ O	0 to 60
Max Resolution	0.1
AC Voltage Finder	100V~600V



EMC
EN: 61326


Features

- Quickly indicates the moisture content of materials
- Moisture index display corresponds of % moisture of wood or material being tested
- Pin-Free sensor's measurement depth of 1.25" (32mm) below the surface
- Low battery indication
- MAX/MIN/HOLD Function
- Power Light Indication
- White Backlit LCD display
- Laser leveling
- 180 degree pivoting laser plane with level and plump vials
- 20 laser line projection onto work surface with 90 degree squaring
- Two self contained hange pins to mount unit to work surface (vertical or horizontal)
- Ergonomically designed for comfort and grip
- Non-contact detection of AC voltage from 100VAC to 600VAC

Laser line & External Level



Non-contact moisture sensor



Size(HxWxD): 180mm x 67mm x 38mm

Weight: 180g

Accessories:

9V battery, gift box with carrying case.

