

EMC  
EN: 61326

You can monitor temperature and humidity values efficiently and conveniently for long time periods by using the Datalogger.

The readings are saved in the logger and simply read out by your PC with USB interface.

Model 171



- Memory for 16000 (171) readings
- Temperature datalogger (170)
- 2000 Counts digital LCD display (171D)
- Freely selectable measurement cycle from 2sec. to 24h
- Battery life: more than 3 years
- Display all status information through two LEDs
- Download collected data through USB interface
- Alarm display if user-defined maximum/minimum values exceed
- Analysis software used to view graph for logging data



Specifications

	170	171/171D	171T
Temp range	-40 to 70°C -40 to 158°F	-40 to 70°C -40 to 158°F	
Temp Accuracy	±1°C	±1°C	
Humidity range		0 to 100%RH	
Humidity Accuracy		±2%RH	
Temp K range			-200 to 1370°C(-328 to 2498°F)
Temp K Accuracy			±1°C
Memory	32000(16000 each for temperature and humidity)		
Measuring rate	2sec. to 24h		
Battery life	typically 3 years		
Analysis software	windows 98/2000/XP/Vista/7		


Accessories :

3.6V Lithium battery, K-Temp probe(171T), software and clamshell.


Size(HxWxD): 130mm x 30mm x 25mm

Weight: 20g

Model 171T



Model 171D





EMC  
 EN: 61326



Model 171VD

Model 171A



Specifications		
	171V/171VD	171A/171AD
DC Voltage range	0 to 30V	
DC Voltage accuracy	±0.5%+1	±0.5%+1
DC Current range		4 to 20mA
DC Current accuracy		±1%±1Count
Reading Memories	32000 readings	32000 readings
Measuring rate	400Hz. to 24h	1sec. to 24h
LCD display counts	2000(171VD)	2000(171AD)
Analysis software	windows 98/2000/XP/Vista/7	

Accessories : 3.6V Lithium battery, software and clamshell.

Size(HxWxD): 130mm x 30mm x 25mm

Weight: 20g