



Model 615



Large LCD display



EMC  
EN: 61326

625 is digital Humidity & Temperature Meter with Wet Bulb Temperature & Dew Point temperature, which has been designed to combine the functions of Humidity Meter, Temperature Meter, Wet Bulb Temperature and Dew point temperature.

It is an ideal Humidity & Temperature Meter with scores of practical applications for laboratorial, industrial, Engineer and professional use.

615 is Humidity meter with Air and type K thermocouple thermometer.



High Performance and quality sensor

- Large, easy-to-read backlit LCD with dual display
- Fast Response Time: 10s (90% at 25°C still air)
- 2% High Accuracy (625)
- Dew Point Temperature (-30°C-100°C/-22°F-199°F) (625)
- Wet Bulb Temperature (0°C-80°C/32°F-176°F) (625)
- Resolution 0.1%RH, 0.1°C/0.1°F
- Max/Min Hold and Data Hold Function (625)
- Microprocessor-based Design (625)
- Dual Display Temperature & Humidity

Model 625



Features

	615	625	616CT
Large dual digital LCD display with backlight	*	*	*
Response Time:10s (90% at +25°C still air)		*	*
Sampling Rate: 2.5 samples per second	*	*	*
Dew Point Temperature & Wet Bulb Temperature		*	*
2% High Accuracy		*	*
Dual Display Temperature & Humidity	*	*	*
Type K temperature	*		
Non-contact IR temperature			*

Model 616CT



Specifications

Function	Range	Resolution	Basic Accuracy	615	625	616CT
Humidity	0°C-100%RH	0.1%RH	±2%RH ±3.5%RH	*	*	*
Temperature	-30°C-100°C/-30°F-199°F	0.1°C/°F	±0.5°C/0.9°F		*	*
Type K Temp.	-20°C-1000°C/-4°F-1832°F	0.1° up to 200°, 1° over 200°	±3%		*	*
Dew Point Temp.	-30°C-100°C/-22°F-199°F	0.1°C/°F	±1.0°C/1.8°F		*	*
Wet Bulb Temp.	0°C-80°C/32°F-176°F	0.1°C/°F	±1.0°C/1.8°F		*	*
IR temp.	-50°C-500°C/-58°F-932°F	0.1° up to 200°, 1° over 200°	±2.0%±2°C/4°F			*

Size(HxWxD): 225mm x 45mm x 34mm

Weight: 200g

Accessories:

Carrying case, type K temperature probe (615) and 9V battery.