

- Highest 2% RH accuracy with fast response time
- Dual backlit display
- Large LCD display of: Humidity/Temperature; Humidity/Dew Point; Humidity/Wet Bulb
- Fast Response time when taking a measurement
- Data Hold and Min/Max functions
- Auto power off and low battery indication



%RH, Temperature, Dew point, Wet bulb, absolute Humidity, Mixing ration

Mixing ration/ Temperature



CE  
EMC  
EN: 61326

Specifications		
Function	Range	Basic Accuracy(%rdg+digits)
Humidity	0°C-10%RH, 90°C-100%RH	±3%RH
	10°C-90%RH	±2%RH
Temperature	-30°C~100°C/-22~199°F	±0.5°C/0.9°F
	-20°C~60°C/-4~140°F	±2°C/4°F
Dew point Temp	-30°C~100°C/-22~199°F	±0.5°C/0.9°F
Wet Bulb Temp	0°C~80°C/32~176°F	±0.5°C/0.9°F

Features	
Fast Response Time	
High Accuracy	
High Performance	
Max Hold and Data Hold Function	
Dual Display & Backlight	
Dew point & Wet Bulb Temperature	

Size(HxWxD): 255mm x 45mm x 34mm  
Weight: 200g

Accessories :  
9V battery and gift box with carrying case