



**TES-1317/1318**

## Platinum RTD Thermometer

### Product Features

- Pt 3916/3926/385 RTD standard.
- 7500 DataLogging capacity. (1317)
- Warning beeper with HI/LO setting.
- Time setting.
- MAX / MIN with TIME, MAX-MIN AVG Hold function.
- °C / °F / K User-Selective.
- Back - Light LCD display.
- Dual input function T1/T2 temperature display. (1318)

<b>Measuring Range</b>	Pt385 -190°C ~ 790°C (-310 ~ 1454°F) Pt3916 -190°C ~ 615°C (-310 ~ 1139°F) Pt3926 -190°C ~ 615°C (-310 ~ 1139°F)
<b>Resolution</b>	0.1°C / 0.1°F / 0.1K
<b>Accuracy</b>	±(0.05%rdg+0.2°C) ±(0.05%rdg+0.4°F)
<b>Datalogger (1317)</b>	7500 reading
<b>Temperature Coefficient</b>	Less that 0.1 times the applicable accuracy specification per °C(°F)
<b>Sampling Rate</b>	1 time/sec
<b>Operating/ Storage Conditions</b>	0°C ~ 40°C < 80% RH , -10°C ~ 60°C < 70%RH
<b>Power Source</b>	6 pcs size AAA Battery
<b>Battery Life</b>	Approx. 300hours. (not including backlight and beeper)
<b>Size</b>	152(L)×72(W)×37(H)mm
<b>Weight</b>	Approx. 300g
<b>Accessories</b>	Instruction manual, Battery