

TES-1330A/1332A/1334A Light Meter



FEATURES

- Spectral Sensitivity close to CIE photo pic Curve
- Cosine Angular corrected
- Analog output jack for recording TES -
1332A/1334A
- Data Hold function, Peak Hold function for 1334



SPECIFICATION

Display	3 1/2 digit LCD
Measuring Range	20/200/2000/20000 Lux 1330A also Footcandle for 1334A 200/2000/20000/200000 Lux 1332A 20000 lux-reading x 10; 200000 lux-reading x 100
Overrange Display	Highest digit of 1 is displayed
Resolution	0.01 Lux 1330A,1334A & 0.1 Lux 1332A
Accuracy	+/- 3% rdg +/- 0.5% f.s.(<10,000 lux +/- 4% rdg +/- 10dgt >10,000 lux calibrated to standard incandescent lamp, 2856 K
Repeatability	±2%
Temperature Characteristics	±0.1%°C
Measuring Rate	Approx. 2 times/sec.
Recorder Output	DC 2V/f.s. (full scale (TES-1332A
Operating Temperature & Humidity	0 ° to 40°C 32°F to 104 °F < 70% R.H.
Power Source	one 9V battery
Dimensions	100mm L x 60mm W x 27mm H
Dimension	135mm L x 72mm W x 33mm H
Weight	250g
Accessories	Carrying case, 9V battery & Instruction Manual