

## TES-3092 AC/DC Clamp Meter

AC/DC Clamp Meter  
MODEL: TES-3092



- Compact Size.
- AC/DC Current Measurement (AC 700A / DC 800A).
- 600 V AC & 200V DC, Ohm/Continuity Beeper.
- One Touch DCA Zero.
- **Possible replacements:** [MTP-3094](#) or [MTP-3096](#)

**SPECIFICATIONS: (23°C ± 5°C)**  
**DC Current:**

Range	Resolution	Accuracy	Overload protection
200A	0.1A	± (1.5% + 2dgts)	850A
800A	1A	± (1.5% + 2dgts)	850A

**AC Current:** (Frequency response: 50Hz to 400Hz)

Range	Resolution	Accuracy	Overload protection
200A	0.1A	± (2.0% + 4dgts)	850A
700A	1A	± (2.0% + 4dgts)	850A

**DC Voltage:** (Input Impedance 1MΩ)

Range	Resolution	Accuracy	Overload protection
200V	0.1V	± (1% + 1dgts)	600V <sub>rms</sub>

**AC Voltage:** (Input Impedance 1MΩ and Frequency Response 50Hz to 400Hz)

Range	Resolution	Accuracy	Overload protection
600V	1V	± (1.5% ± 4dgts)	600V <sub>rms</sub>

**Resistance:** (Open circuit voltage 3V)

Range	Resolution	Accuracy	Overload Protection
2kΩ	1Ω	± (1% + 2dgts)	600V <sub>rms</sub>

**General specifications:**

Applicable standards	EN 61010-2-032, EN 61010-1, Pollution Degree 2
Jaw opening	27mm maximum
Display	3½ digit LCD with maximum reading of 1999
Operating temperature	0°C to 50°C
Dimensions	192(L) x 64(W) x 31(H)mm, (7.6" x 2.5 x 1.2")
Weight	240g (batteries included), 8.5oz
Accessories included	Instruction Manual, 9V Battery, Test Leads, Carrying Case