



AFLEX 3003 Flexible VA Harmonics Tester

Electrical Specifications: (23°C±5°C)

AC Current (50 or 60 Hz, Auto Range, True RMS, Crest Factor<4, CT=1)

Range	Resolution	Accuracy of Readings
0 – 300.0A	0.1A	±1% of range
300.0 – 999.9A	0.1A	±1% of range
1000 – 3000 A	1 A	±1% of range

AC Voltage (50/60 Hz, Auto Range, TRMS, C.F.<4, Overload Protection AC 800V)

Range	Resolution	Accuracy of Readings
4.0 V – 600.0 V	0.1 V	±0.5% ± 5dgts

Harmonics of AC Voltage in Percentage

Range	Resolution	Accuracy
1 – 20 th	0.1%	±2%
21 – 50 th	0.1%	4% of reading ±2.0%

Harmonics of AC Voltage in Magnitude

Range	Resolution	Accuracy
1 – 20 th	0.1%	±2% ± 0.5V
21 – 50 th	0.1%	4% of reading ±0.5V

Harmonics of AC Current in Percentage

Range	Resolution	Accuracy
1 – 20 th	0.1%	±2%
21 – 50 th	0.1%	4% of reading ±2.0%

Harmonics of AC Current in Magnitude

Range (0 – 300A)	Resolution	Accuracy
1 – 20 th	0.1%	±2% of reading ±0.4A
21 – 50 th	0.1%	±4% of reading ±0.4A

Harmonics of AC Current in Magnitude

Range	Resolution	Accuracy
1 – 20 th	0.1%	±2% of reading ±40A
21 – 50 th	0.1%	±4% of reading ±40A

Phase Angle (Φ , V > 20V, A > 30A)

Range	Resolution	Accuracy
-180° to 180°	0.1°	± 1°
0° to 360°	0.1°	± 1°

Total Harmonic Distortion

Range	Resolution	Accuracy
0.0 – 20%	0.1%	± 2%
20 – 100%	01%	± 6% of reading ± 1%
100 – 999.9 %	0.1%	± 10% of reading ± 1%

Peak Value of AC Voltage (RMS value > 10V) or AC Current (RMS value > 30A)

Range	Sampling Time	Accuracy of Reading
50 Hz	39 μ s	± 5% ± 30 digits
60 Hz	33 μ s	± 5% ± 30 digits


Crest Factor (C.F.) of ACV (RMS value > 10V) or ACA (RMS value > 30A)

Range	Resolution	Accuracy of Readings
1.00 – 99.99	0.01	± 5% ± 30 digits

Frequency of ACV (RMS value > 10V) or ACA (RMS value > 30A)

Range	Resolution	Accuracy
45 – 65	0.1	± 0.2Hz

General Specifications:

Probe Length: 3000-24	24 in / 610 mm
Minimum Bending Diameter:	35mm
Connector Diameter:	23mm
Cable Diameter:	14mm
Cable Length from Probe to Box:	1700mm
Cable Length from Box to Output:	1700mm
Dimension (Box):	130mm(L) x 80mm(W)x 43mm(H) 5.1"(L) x 3.1"(W) x 1.7"(H)
Battery Type:	two 1.5V SUM-3
Battery life:	200hrs @ 2000mAH.
Display:	4+4 digits LCD
Range Selection:	Auto
Overload Indication:	OL
Power Consumption:	10mA(approx.)
Low battery Indication:	
Auto-Power-Off:	30 minutes after power-on
LCD Update Time:	2 times/sec.
No. Of Samples per Period	512 (voltage or current) 256 (power)
Data logging memory size:	8000 records
Data logging sampling time:	0~600 sec
Data logging period:	8000 x sampling time (0~600 sec.)
Operating Temperature:	-10°C to 85°C
Operating Humidity:	15% to 85% RH
Altitude:	up to 2000M
Storage Temperature:	-20°C to 85°C
Storage Humidity:	15% to 85% RH
Weight:	430g (battery included)
Accessories:	Test leads Carrying case x 1 Users manual x 1 Batteries 1.5V x 2

PROVA[®]

PROVA INSTRUMENTS INC.

Add: 6F-2, #129, Lane 235, Pao-Chiao Road,
Shin-Tien, Taipei Hsien 231, Taiwan

Tel: 886-2-89191255

Fax: 886-2-89191489

E-mail: prova@ms3.hinet.net