



## AFLEX 3005

### Flexible Power Quality Tester

**Electrical Specifications: (23°C±5°C)**

**AC Watt** (50 or 60 Hz, PF 0.5 to 1, CT=1, V>AC 5V, Current>AC 5A for A range)

Range (0 to 3000A)	Resolution	Accuracy of Readings	
		> 20 V and > 30A	< 20V or < 30A
10.0 – 999.9 W	0.1W	±1% of range	±2% of range
1.000 – 9.999 KW	0.001 KW	±1% of range	±2% of range
10.00 – 99.99 KW	0.01 KW	±1% of range	±2% of range
100.0 – 999.9 KW	0.1 KW	±1% of range	±2% of range
1000 – 9999 KW	1 KW	±1% of range	±2% of range

**AC Apparent Power** (VA, from 0.000VA to 9999 KVA)

Range (0 to 3000A)	Resolution	Accuracy of Readings	
		> 20 V and > 30A	< 20V or < 30A
10.0 – 999.9 VA	0.1VA	±1% of range	±2% of range
1.000 – 9.999 KVA	0.001 KVA	±1% of range	±2% of range
10.00 – 99.99 KVA	0.01 KVA	±1% of range	±2% of range
100.0 – 999.9 KVA	0.1 KVA	±1% of range	±2% of range
1000 – 9999 KVA	1 KVA	±1% of range	±2% of range

**AC Reactive Power** (VAR, from 0.000 VAR to 9999 KVAR)

Range (0 to 3000A)	Resolution	Accuracy of Readings	
		> 20 V and > 30A	< 20V or < 30A
10.0 – 999.9 VAR	0.1VAR	±1% of range	±2% of range
1.000 – 9.999 KVAR	0.001 KVAR	±1% of range	±2% of range
10.00 – 99.99 KVAR	0.01 KVAR	±1% of range	±2% of range
100.0 – 999.9 KVAR	0.1 KVAR	±1% of range	±2% of range
1000 – 9999 KVAR	1 KVAR	±1% of range	±2% of range

**Power Factor (PF)**

Range	Resolution	Accuracy	
		> 20V and > 30A	< 20V or < 30A
0.000 – 1.000	0.001	± 0.04	±0.1

**AC Current** (50 or 60 Hz, Auto Range, True RMS, Crest Factor<4, CT=1)

Range	Resolution	Accuracy of Readings
0 – 300.0A	0.1A	±1% of range
300.0 – 999.9A	0.1A	±1% of range
1000 – 3000 A	1 A	±1% of range

**AC Voltage** (50/60 Hz, Auto Range, TRMS, C.F.<4, Overload Protection AC 800V)

Range	Resolution	Accuracy of Readings
4.0 V – 600.0 V	0.1 V	±0.5% ± 5dgt

**Harmonics of AC Voltage in Percentage**

Range	Resolution	Accuracy
1 – 20 <sup>th</sup>	0.1%	±2%
21 – 50 <sup>th</sup>	0.1%	4% of reading ±2.0%

**Harmonics of AC Voltage in Magnitude**

Range	Resolution	Accuracy
1 – 20 <sup>th</sup>	0.1%	±2% ± 0.5V
21 – 50 <sup>th</sup>	0.1%	4% of reading ±0.5V

**Harmonics of AC Current in Percentage**

Range	Resolution	Accuracy
1 – 20 <sup>th</sup>	0.1%	±2%
21 – 50 <sup>th</sup>	0.1%	4% of reading ±2.0%

**Harmonics of AC Current in Magnitude**

Range (0 – 300A)	Resolution	Accuracy
1 – 20 <sup>th</sup>	0.1%	±2% of reading ±0.4A
21 – 50 <sup>th</sup>	0.1%	±4% of reading ±0.4A

**Harmonics of AC Current in Magnitude**

Range	Resolution	Accuracy
1 – 20 <sup>th</sup>	0.1%	±2% of reading ±40A
21 – 50 <sup>th</sup>	0.1%	±4% of reading ±40A

**Phase Angle (Φ, V > 20V, A > 30A)**

Range	Resolution	Accuracy
-180° to 180°	0.1°	± 1°
0° to 360°	0.1°	± 1°

**Total Harmonic Distortion**

Range	Resolution	Accuracy
0.0 – 20%	0.1%	± 2%
20 – 100%	01%	± 6% of reading ± 1%
100 – 999.9 %	0.1%	± 10% of reading ± 1%

**Peak Value of AC Voltage** (RMS value > 10V) **or AC Current** (RMS value > 30A)

Range	Sampling Time	Accuracy of Reading
50 Hz	39 μs	± 5% ± 30 digits
60 Hz	33 μs	± 5% ± 30 digits


**Crest Factor (C.F.) of ACV** (RMS value > 10V) **or ACA** (RMS value > 30A)

Range	Resolution	Accuracy of Readings
1.00 – 99.99	0.01	± 5% ± 30 digits

**Frequency of ACV** (RMS value > 10V) **or ACA** (RMS value > 30A)

Range	Resolution	Accuracy
45 – 65	0.1	± 0.2Hz

## General Specifications:

Probe Length: 3005-24	24 in / 610 mm
Minimum Bending Diameter:	35mm
Connector Diameter:	23mm
Cable Diameter:	14mm
Cable Length from Probe to Box:	1700mm
Cable Length from Box to Output:	1700mm
Dimension (Box):	130mm(L) x 80mm(W)x 43mm(H) 5.1"(L) x 3.1"(W) x 1.7"(H)
Battery Type:	two 1.5V SUM-3
Battery life:	200hrs @ 2000mAH.
Display:	4+4 digits LCD
Range Selection:	Auto
Overload Indication:	OL
Power Consumption:	10mA(approx.)
Low battery Indication:	
Auto-Power-Off:	30 minutes after power-on
LCD Update Time:	2 times/sec.
No. Of Samples per Period	512 (voltage or current) 256 (power)
Data logging memory size:	8000 records
Data logging sampling time:	0~600 sec
Data logging period:	8000 x sampling time (0~600 sec.)
Operating Temperature:	-10°C to 85°C
Operating Humidity:	15% to 85% RH
Altitude:	up to 2000M
Storage Temperature:	-20°C to 85°C
Storage Humidity:	15% to 85% RH
Weight:	430g (battery included)
Accessories:	Test leads Carrying case x 1 Users manual x 1 Batteries 1.5V x 2 Software CD x 1 Software manual x 1



**PROVA INSTRUMENTS INC.**

**Add:** 6F-2, #129, Lane 235, Pao-Chiao Road,  
Shin-Tien, Taipei Hsien 231, Taiwan

**Tel:** 886-2-89191255

**Fax:** 886-2-89191489

**E-mail:** [prova@ms3.hinet.net](mailto:prova@ms3.hinet.net)