

**AG Series** Dual-channel Arbitrary Waveform Generator



- + Advanced DDS technology, max 60MHz frequency output
- + Up to 250MS/s sample rate, and 1μHz frequency resolution
- + Vertical Resolution : 14 bits, up to 1M arb waveform length
- + Comprehensive waveform output : 5 basic waveforms, and 45 built-in arbitrary waveforms
- + Comprehensive modulation functions : AM, FM, PM, FSK, PWM, Sweep, and Burst
- + High-accuracy frequency counter integrated, supported range 100mHz - 200MHz
- + Supported SCPI
- + 4 inch high resolution (480 × 320 pixels) TFT LCD display

**+ Performance Specifications**

Model	AG1012	AG1012F	AG1022	AG1022F	AG2052F <small>NEW!</small>	AG2062F <small>NEW!</small>
Channel	dual					
Frequency Output	10MHz		25MHz		50MHz	60MHz
Sample Rate	125MS/s			250MS/s		
Vertical Resolution	14 bits					

**Waveform**

Standard Waveform	Sine, Square, Pulse, Ramp, and Noise
Arbitrary Waveform	Exponential Rise, Exponential Fall, Sin(x)/x, Step Wave, and others, total 45 built-in waveforms, and user-defined arbitrary waveform

**Frequency (resolution 1μHz)**

Sine	1μHz - 10MHz	1μHz - 25MHz	1μHz - 50MHz	1μHz - 60MHz
Square	1μHz - 5MHz		1μHz - 25MHz	1μHz - 30MHz
Pulse	1μHz - 5MHz		1μHz - 10MHz	
Ramp	1μHz - 1MHz			
Noise	25MHz (-3dB) (typical)			
Arbitrary Waveform	1μHz - 10MHz			

**Amplitude**

Amplitude	1m Vpp - 10 Vpp (50Ω), 1m Vpp - 20 Vpp (high impedance)
Resolution	1m Vpp or 14 bits
DC Offset Range (AD+DC)	±5V (50Ω), ±10V (high impedance)
DC Offset Range Resolution	1mV
Load Impedance	50Ω (typical)

Model	AG1012	AG1022	AG1012F	AG1022F	AG2052F <small>NEW!</small>	AG2062F <small>NEW!</small>
<b>Arbitrary Waveform</b>						
Wave Length	2 pts to 8K pts			2 pts to 1M pts		
Sample Rate	125MS/s			250MS/s		
Vertical Resolution	14 bits					
Non-volatile Memory	26 waveforms					
<b>Modulation</b>						
Modulation Waveform	/		AM, FM, PM, FSK, Sweep, and Burst	AM, FM, PM, FSK, PWM, Sweep, and Burst		
Modulation Frequency	/		2mHz to 20.00KHz (FSK 1μHz - 100KHz)			
<b>Counter</b>						
Function	/		Frequency Period, +Width, -Width, +Duty, and -Duty			
Frequency Range	/		100mHz - 200MHz			
Frequency Resolution	/		6 digits			
<b>Input / Output</b>						
Display	4 inch (480 × 320 pixels) TFT LCD					
Type	external reference clock input / output		counter external modulation input / output, external trigger input / output, external reference clock input / output			
Communication Interface	USB host, USB device, RS232					
<b>Mechanical</b>						
Dimension (W×H×D)	235 × 110 × 295 (mm)					
Weight (without package)	3.00 kg					


Specifications subject to change without prior notice.

**+ Application**

design and debug    circuit function test    education and training

**+ Accessories**

The accessories subject to final delivery.



Power Cord    CD Rom    Manual    USB Cable    Q9