

Model 3310

3310 Series Professional 1000A AC Clamp Meters provide many functions for professional AC current and voltage measurements including resistance, capacitance and diode test, etc. With mid-size and tear-drop shaped jaw, it is easy to use in crowded cable areas and other tight places.

Features

	3310	3311
Current measurements	AC	AC
Digital display counts	4000	4000
Electronic overload protection	*	*
Continuity buzzer & Diode check	*	*
Data Hold function	*	*
Auto Power Off	*	*
Low battery indication	*	*
Display with backlight	*	*
2.16" (55mm) Clamp jaw opening	*	*

Specifications

Function	Max. Range	Basic Accuracy	Max. Resolution	3310	3311
AC Current	1000A	±(2.5%+5d)	100mA	*	*
AC Voltage	1000V	±(1.0%+4d)	0.1mV	*	*
DC Voltage	1000V	±(0.5%+4d)	0.1mV	*	*
Resistance	40MΩ	±(1.0%+2d)	0.1Ω	*	*
Capacitance	40mF	±(3.0%+5d)	0.01nF	*	*
Frequency	10MHz	±(1.2%+2d)	0.001Hz	*	*



EMC & LVD
EN: 61326
EN: 61010-1, EN: 61010-02-031



Model 3311

Size(HxWxD): 270mm x 107mm x 50mm
Weight: 554g

Accessories:
Test leads, gift box with carrying case, 9V battery.



Model 3313

3312/3313/3315/3316 Series Professional 2000A AC, AC/DC Clamp Meters provide many functions for professional AC, AC/DC measurements including resistance, capacitance and diode test, etc. With mid-size and tear-drop shaped jaw, it is easy to use in crowded cable areas and other tight places.



EMC & LVD
EN: 61326
EN: 61010-1, EN: 61010-02-031



Model 3315

Features

	3312	3313	3315	3316
Current measurements	AC	AC/DC	AC/DC	AC/DC
True RMS measurements		*	*	*
Digital display counts	4000	4000	4000	4000
Electronic overload protection	*	*	*	*
Continuity buzzer & Diode check	*	*	*	*
Data Hold function	*	*	*	*
Peak Hold	*	*	*	*
DCA Zero function	*	*	*	*
Auto Power Off	*	*	*	*
Low battery indication	*	*	*	*
Display with backlight	*	*	*	*
2.16" (55mm) Clamp jaw opening	*	*	*	*

Specifications

Function	Max. Range	Basic Accuracy	Max. Resolution	3312	3313	3315	3316
AC Current	2000A	±(2.5%+5d)	100mA	*	*	*	*
DC Current	2000A	±(2.5%+5d)	100mA	*	*	*	*
AC Voltage	1000V	±(1.0%+4d)	0.1mV	*	*	*	*
DC Voltage	1000V	±(0.5%+4d)	0.1mV	*	*	*	*
Resistance	40MΩ	±(1.0%+2d)	0.1Ω	*	*	*	*
Frequency	10MHz	±(1.2%+2d)	0.001Hz	*	*	*	*



Size(HxWxD): 270mm x 107mm x 50mm
Weight: 554g

Accessories:
Test leads, gift box with carrying case, 9V battery.



Model 3312