

DT-9380/9380A/9381/9381A/9382

Professional 1000A AC, AC/DC True RMS Clamp Meters with TFT color LCD display

CEM



The 9380/9381/9382/9383 series clamp meters providing fast A/D converting sampling time, high accuracy, built-in datalogging offer all needed features for measurement. It is with modern bodies and jaws design for perfect handheld and tight place testing. A large backlit display (on most models) is easy to see and a handy data hold keeps measurements on the display.

- Double molded plastic housing
- True RMS measurement for ACV & ACA
- Flexible current probe expands the measurement range to 3000 ACA (9383)



EMC & LVD
EN: 61326
EN: 61010-1
EN: 61010-02-032
EN: 61010-02-033



Features

	9380	9380A	9381	9381A	9382	9383
Current measurement	AC	AC	AC/DC	AC/DC	AC/DC	AC/DC
Display counts	4000	6000	4000	6000	6000	50000
1.8" TFT color LCD display counts					*	*
AC True RMS	*	*	*	*	*	*
10kHz bandwidth (voltage/current)						*
Data Hold & Peak Hold	*		*	*	*	*
Max /Min Hold	*		*		*	*
REL (Zero) Function			*	*	*	*
Flashlight and Backlight	*	*	*	*	Flashlight	Flashlight
Auto Power Off	*	*	*	*	*	*
Low battery indication	*	*	*	*	*	*
100ms Inrush current	*		*	*	*	*
Low input impedance prevents false readings due to "ghost voltage" (LoZ)	*		*	*	*	*
Low pass filter for accurate measurement of variable frequency drive (VFD) signals		*		*	*	*
1.9" (48mm) Jaw opening	*	*	*	*	*	*
Bluetooth interface					*	*
3000A ACA flexible clamp					*	*
Trend capture function					*	*
Fast response time				10 times/sec.	20 times/sec.	
100 Graph Data review					*	*
NCV Function	*	*	*	*	*	*

Specifications

Function	Max Range	Basic Accuracy	9380	9380A	9381	9381A	9382	9383
Voltage DC	1000V	$\pm(0.5\%+2d)$	*	*	*	*	*	$\pm(0.09\%+2d)$
Voltage AC	1000V	$\pm(1.0\%+5d)$	*	*	*	*	*	$\pm(0.5\%+5d)$
Current DC	1000A	$\pm(2.0\%+5d)$			*	*	*	$\pm(2.0\%+5d)$
Current AC	1000A	$\pm(2.5\%+8d)$	*	*	*	*	*	$\pm(2.5\%+8d)$
ACA flexible	3000A	$\pm(2.5\%+8d)$					*	$\pm(2.5\%+8d)$
Resistance	60MΩ	$\pm(3.0\%+5d)$	40MΩ	*	40MΩ	*	*	$\pm(2.0\%+5d)$
Temperature	1000°C/1832°F	$\pm(1.0\%+3d)$	*	*	*	*	*	$\pm(1.0\%+3d)$
Capacitance	100mF	$\pm(2.5\%+5d)$	*	*	*	*	*	$\pm(2.5\%+5d)$
Frequency	10kHz	$\pm(0.5\%+2d)$	*	*	*	*	*	$\pm(0.5\%+2d)$
Inrush Current	1000A	$\pm(2.5\%+2d)$		*		*	*	$\pm(2.5\%+2d)$
Continuity check	Buzzer sounds at 50Ω							
Diode test	Test current 0.3mA							

Size(HxWxD): 250mm x 78mm x 40mm

Weight: 350g

Accessories:

Test leads, gift box with carrying case, Temperature probe and 1.5V AAA x 3 batteries(9380/9381/9380A/9381A)

Li-ion battery, Software(9382/9383) Flexible clamp (9383)

- Fast response time
- True RMS

- TFT color LCD display (9382/9383)
- PC Calibration



Model 9380



Model 9381



Flexible clamp (optional)



Model DT-320BS

Model 9382