



**GD-3308
Detector de Gases**



GD-3306/3308

Combustible Gas Leak Detector

3306/3308 Combustible Gas Leak Detector detects the presence of combustible gas and measures concentrations between 0~10000 parts per million (PPM). The Detector indicates the presence of combustible gas by a reading on the LCD (3308) or five red LEDs (3306), The five red LEDs indicate different concentration of gas. The beeper function much like clicking of a Geiger counter: Above 3200 PPM, the beeper sounds continuously with the concentration of gas. From 0 PPM to 3200 PPM, the beeper will sound rapidly due to the increasing concentrations of combustible gas. It provides quick, precise gas leak locating, would be the best instrument for explosion preventing and safe production.

<i>Features</i>		
	3306	3308
<i>Digital LCD Display</i>		*
<i>Visible, audible and vibration alarm for noisy & bright environments</i>	*	
<i>Highly sensitive and reliable</i>	*	*
<i>Pinpoint small Leaks: Detects all combustible gas leaks even tiny leaks</i>	*	*
<i>Auto Zero</i>	*	*
<i>Highly Accuracy, quick response</i>	*	*
<i>16"inch flexible probe with replaceable sensor</i>	*	*
<i>Auto power off</i>	*	*

<i>Specifications</i>			
		3306	3308
<i>Sensitivity</i>	<i><50ppm(methane)</i>	*	*
<i>Range</i>	<i>0~10000ppm(methance)</i>	*	*
<i>Response Time</i>	<i><2 secs</i>	*	*
<i>Warm-Up Time</i>	<i>Approx. 40 secs</i>	*	*
<i>Audible Alarm</i>	<i>>75 db</i>	*	*
<i>Vibration Alarm</i>	<i>Standard</i>	*	*
<i>Probe Length</i>	<i>16"inch</i>	*	*
<i>Visual Alert</i>	<i>5 Red LEDs: Gas Measuring Levels; Sensitivity Visual Alert</i>	*	
<i>Display Type</i>	<i>LCD</i>		*
<i>Audible Alert(>75 db)</i>	<i>Loud Audible Ticking Rate(w/Continuous Modulation Proportional to Gas Level)</i>	*	*

