

HDS Series Handheld Digital Storage Oscilloscope



- + 2 in 1 (DSO + Multimeter)
- + Auto-scale function
- + 20 automatic measurements
- + Bandwidth : 20MHz - 60MHz
- + USB data transmission supported
- + Rechargeable Li-ion battery (6 hours' backup)



+ Performance Specifications

Model	HDS1021M	HDS1022M	HDS2062M
Bandwidth	20MHz	20MHz	60MHz
Sample Rate (real time)	100MS/s	100MS/s	250MS/s
Horizontal Scale (s/div)	5ns/div - 100s/div, step by 1 - 2.5 - 5		5ns/div - 100s/div, step by 1 - 2 - 5
Rise Time (at input, typical)	≤17.5ns		≤5.8ns
Display	3.5" color LCD, 320 x 240 pixels		3.7" color LCD, 640 x 480 pixels
Channel	single		dual
Input Impedance	1MΩ ± 2%, in parallel with 18pF ± 5pF		1MΩ ± 2%, in parallel with 20pF ± 5pF
Record Length	max 6K points on each channel		
Interpolation	sin(x)/x		
Probe Attenuation Factor	1X, 10X, 100X, 1000X		
Input Coupling	DC, AC, and GND		
DC Accuracy (average)	average > 16 : ± (3% reading + 0.05div) for ΔV		average > 16 : ± (5% reading + 0.05div) for ΔV
Vertical Sensitivity	5mV/div - 5V/div (at input)		
Vertical Resolution (A/D)	8 bits		
Max Input Voltage	400V (PK - PK) (DC + AC, PK - PK, 1MΩ input impedance, probe attenuation 10 : 1), CAT II		
Trigger Type	Edge, Video		
Trigger Mode	Auto, Normal, Single		
Trigger Level	± 6 divisions from screen center		
Acquisition Mode	Sample, Peak Detect, and Average		
DC Gain Accuracy	± 3%		± 5%

Model	HDS1021M	HDS1022M	HDS2062M
Automatic Measurement	Vpp, Vavg, Vrms, Freq, Period, Vmax, Vmin, Vtop, Vbase, Vamp, Overshoot, Preshoot, Rise Time, Fall Time, Delay A→B, Delay A→B, +Width, -Width, +Duty, -Duty		
Waveform Math	/	+, -, ×, ÷, invert	
Waveform Storage	4 waveforms		
Lissajous Figure	Bandwidth	/	full bandwidth
	Phase Difference	/	±3 degrees
Communication Interface	USB		
Power Supply	100V - 240V AC, 50/60Hz		
Li-ion Battery	7.4V, 6 hours' operation		
Dimensions (W × H × D)	115 × 180 × 40 (mm)		
Weight (without package)	645 g		

+ Multimeter Specifications

Full Scale Reading	3 ³ / ₄ digits (max 4000 count)	Diode	0V - 1.5V
Input Impedance	10 MΩ	On / Off Test	<50 (± 30) beeping
Voltage	VDC : 400mV, 4V, 40V, 400V, 1000V : ±(1% ± 1 digit); max input : DC 1000V VAC : 4V, 40V, 400V : ±(1% ± 3 digits), 750V : ±(2% ± 3 digits); Frequency : 40Hz - 400Hz; max input : AC 400V (virtual value)		
Current	DC : 40mA, 400mA : ±(1.5% ± 1 digit), 20A : ±(3% ± 3 digits) AC : 40mA : ±(1.5% ± 3 digits), 400mA : ±(2% ± 1 digit), 20A : ±(5% ± 3 digits)		
Impedance	400Ω : ±(1% ± 3 digits), 40KΩ - 4MΩ : ±(1% ± 1 digit), 40MΩ : ±(1.5% ± 3 digits)		
Capacitance	51.2nF - 100uF : ±(3% ± 3 digits)		

Specifications subject to change without prior notice.

+ Application

electronic circuit debugging education and training circuit testing design and manufacture
automobile maintenance and testing

+ Accessories

The accessories subject to final delivery.

