

HI2300

Autoranging Bench Meter

EC, TDS, Salinity and Temperature



- **ATC**
 - Automatic temperature compensation
- **Methods**
 - Measures EC, TDS, salinity and temperature
- **One-point calibration**
 - One-point EC and salinity calibration
- **Sensor Check™**
 - Potentiometric probe with built-in temperature sensor
- **Connectivity**
 - PC compatible via USB
- **GLP Features**
 - Meets Good Laboratory Practices

The HI2300 measures EC, TDS, salinity and temperature. In EC and TDS ranges (up to 500 mS/cm and 400 g/L respectively) the instrument automatically chooses the best scale to maintain the highest accuracy.

EC calibration is a one-point procedure. Selectable calibration points are 0.00 µS/cm, 84.0 µS/cm, 1413 µS/cm, 5.00 mS/cm, 12.88 mS/cm, 80.0 mS/cm, and 111.8 mS/cm selected according with the expected measurement range. Salinity calibration is a one-point procedure at 100.0% NaCl. Use HI7037 calibration solution as a 100% NaCl standard solution.

This instrument utilizes a four ring potentiometric probe with platinum sensors to offer versatility over typical amperometric designs. By utilizing the four ring-method, it is possible to measure very low or high conductivity levels without changing probes.

Three options of compensating for temperature are available for this instrument:

Automatic (ATC): The EC probe has a built-in temperature sensor which is used to automatically compensate the EC/TDS reading (from -20.0°C to 120.0°C), using the selected reference temperature (20 or 25°C) and temperature compensation coefficient from (0.0 to 6.0%)/°C.

Manual (MTC): The temperature value, shown on the secondary LCD, can be manually set with the ARROW keys. The compensation is referenced at the selected temperature. All the other parameters of temperature compensation are settable similar to ATC.

No Compensation (NoTC): For actual conductivity or TDS measurement, the temperature value shown on the secondary LCD is not taken into account.

Cell constant is selectable between 0.5 and 1.700. TDS factor is selectable between 0.40 and 0.80.

The HI2300 also provides users with GLP capabilities. Good Laboratory Practice (GLP) is a set of functions that allows storage and retrieval of data regarding the status of the system. After a successful calibration, the meter automatically stores the date and time of calibration, the calibration solution used, the calibration offset and the resulting cell constant value. All this information can be later recalled by the user. Other features include a lock range function and stability indicator.

For PC communication, use the optional HI92000 software and HI920013 USB cable. The software is provided with an exclusive online guide of all the commands available and allows data printing, plotting and exporting.

On-screen Features



Last calibration date



Last calibration year



Last calibration time



Cell constant value (K)



Offset value

Specifications

HI2300

EC	Range	0.00 to 29.99 $\mu\text{S}/\text{cm}$; 30.0 to 299.9 $\mu\text{S}/\text{cm}$; 300 to 2999 $\mu\text{S}/\text{cm}$; 3.00 to 29.99 mS/cm ; 30.0 to 200.0 mS/cm ; up to 500.0 mS/cm (actual EC)*
	Resolution	0.01 $\mu\text{S}/\text{cm}$; 0.1 $\mu\text{S}/\text{cm}$; 1 $\mu\text{S}/\text{cm}$; 0.01 mS/cm ; 0.1 mS/cm
	Accuracy	$\pm 1\%$ of reading \pm (0.05 $\mu\text{S}/\text{cm}$ or 1 digit)
TDS	Range	0.00 to 14.99 mg/L (ppm); 15.0 to 149.9 mg/L (ppm); 150 to 1499 mg/L (ppm); 1.50 to 14.99 g/L (ppt); 15.0 to 100.0 g/L (ppt); up to 400.0 g/L (actual TDS)*, with 0.80 conversion factor
	Resolution	0.01 mg/L ; 0.1 mg/L ; 1 mg/L ; 0.01 g/L ; 0.1 g/L
	Accuracy	$\pm 1\%$ of reading \pm (0.03 mg/L or 1 digit)
Salinity	Range	0.0 to 400.0% NaCl
	Resolution	0.1%
	Accuracy	$\pm 1\%$ of reading
Temperature**	Range	-20.0 to 120.0°C
	Resolution	0.1°C
	Accuracy	$\pm 0.4^\circ\text{C}$
Additional Specifications	EC Calibration	automatic, one point with six memorized values (84, 1413, 5000, 12880, 80000, 111800 $\mu\text{S}/\text{cm}$)
	NaCl Calibration	one point, with HI7037 calibration solution (optional)
	Temperature Calibration	two point, at 0 and 50°C
	Temperature Compensation	automatic or manual from -20.0 to 120.0°C, disabled
	Temperature Coefficient	selectable from 0.00 to 6.00%/°C (EC and TDS only)
	TDS Conversion Factor	selectable from 0.40 to 0.80 (default value: 0.50)
	Probe	HI76310 platinum, four ring conductivity/TDS probe with internal temperature sensor and 1 m (3.3') cable (included)
	PC Connectivity	opto-isolated USB
	Logging	log on demand, 500 samples
	Auto-off	after five minutes of non-use (can be disabled)
	Power Supply	12 VDC adapter (included)
	Environment	0 to 50°C (32 to 122°F); RH max 95%
	Dimensions	235 x 222 x 109 mm (9.2 x 8.7 x 4.3")
Weight	1.3 kg (2.9 lbs.)	
Ordering Information	HI2300-01 (115V) and HI2300-02 (230V) is supplied with HI76310 conductivity probe, 12 VDC adapter and instructions.	

EC, TDS and salinity solutions begin on page 6.42

* with temperature compensation function disabled

(**) Reduced to actual sensor limits

