


DIGITAL MULTIMETER MS8216

MS8216

VOLTAGE AC 600V
DC 600V



Specifications

MS8216

Specifications	Range	Accuracy
DC Voltage	400mV/4V/40V/400V/600V	±(0.7%+2)
AC Voltage	4V/40V/400V/600V	±(0.8%+3)
Resistance	400Ω/4KΩ/40KΩ/400KΩ/4MΩ 40MΩ	±(1.2%+2) ±(2.0%+5)
Capacitance	4nF/40nF/400nF/4μF/40μF/200μF	±(3.0%+3)
Frequency	9.999Hz	±(2.0%+5)
	99.99Hz/999.9Hz/9.999kHz	±(1.5%+5)
	99.99kHz/199.99kHz	±(2.0%+5)
	>200kHz	Take it only as reference
Duty Cycle	0.1%~99.9%	±3.0%
Features		
Display	counts	4000
Auto Ranging	Auto & manual	●
APO	Auto Power Off	●
REL	Relative Measurement	●
Diode	2.7V	●
Continuity Buzzer	<40Ω	●
LBD	Low Battery Display	●
Data Hold		●
General		
Power Supply	357A(LR44) Battery/1.5V×2 Batteries	
Product Size	110mm×76mm×11mm/4.3"×3.07"×0.47"	
Product Weight	85g/0.19lb	
Safety Rating	ETL CAT II 600V RoHS	