

## DIGITAL MULTIMETER MS8360F / MS8360G



Specifications		MS8360F	MS8360G
DC Voltage	400mV/4V/40V/400V 600V	±(0.5%+2) ±(0.8%+2)	±(0.5%+3) ±(0.8%+3)
AC Voltage	400mV 4V/40V/400V 600V	±(1.2%+20) ±(0.8%+3) ±(1.0%+5)	±(2.0%+3) ±(0.8%+3) ±(1.0%+3)
DC Current	400µA/4000µA/40mA/400mA 1A/10A 4A/10A	±(1.0%+5) ±(1.5%+8)	±(0.8%+2) ±(1.2%+2)
AC Current	400µA/4000µA/40mA/400mA 1A/10A 4A/10A	±(1.0%+8) ±(2.0%+10)	±(1.5%+2)
Resistance	400Ω 4kΩ/40kΩ/400kΩ/4MΩ 40MΩ	±(1.0%+3) ±(1.2%+15)	±(0.8%+1) ±(1.0%+2)
Capacitance	40nF/400nF/4µF/200µF 40/400nF/4/40/400/4000µF	±(4.0%+15)	±(3.0%+5)
Frequency	9.999/99.99/999.9Hz/9.999/ 99.99/999.9kHz/9.999MHz	±(4.0%+15)	±(0.5%+2)
Duty Cycle	1%~99%	±(2.0%+2)	±(2.0%+2)
Temperature	-20°C~0°C 1°C~400°C 401°C~1000°C		±(5.0%+4) ±(1.0%+3) ±(2.0%+2)
<b>Features</b>			
Display	counts	4000	4000
Auto Ranging	Auto and Manual	●	●
APO	Auto Power Off	●	●
REL	Relative Measurement	●	●
NCV	Non-Contact Voltage Detector	●	●
Transistor hFE	0~1000	●	●
Diode	2.7V	●	●
Continuity Buzzer	<60Ω	●	●
MAX/MIN			●
Bar Graph			●
Data Hold		●	●
Display Backlight		●	●
LBD	Low Battery Display	●	●
<b>General</b>			
Power Supply	1x9V6F22 Battery		
Product Size	188mm×92mm×50mm/7.4"×3.6"×2.0"		
Product Weight	380g/0.83lb		
Safety Rating	CE ETL CAT III 600V RoHS		

● Feature Difference



### MS8360F

**VOLTAGE** AC 600V  
DC 600V

**CURRENT** AC 10A  
DC 10A



### MS8360G

**VOLTAGE** AC 600V  
DC 600V

**CURRENT** AC 10A  
DC 10A

