


# Laserliner®

## MultiMeter-Compact



Compact universal multimeter with all functions for professionals

Rev. 0910



- Fast and precise **voltage, current, resistance, capacitance, frequency and duty factor measurement**
- **Automatic range changeover and manual range preselection**
- **Automatic continuity tester** with acoustic signal
- **Diode test function** for determining integrity and polarity
- **Integrated contactless voltage indicator** with acoustic, visual and vibration warning
- **High measurement resolution** for precisely determining different measurement variables
- **Data HOLD function** for measuring in inaccessible places
- **CAT III - 1000 V** – can be used for measurements throughout building installations
- Large, easy-to-read **LC display with back-lighting**
- **Compact, impact-resistant enclosure with base support and selector switch**

### TECHNICAL DATA

<b>MAX. INPUT VOLTAGE</b> 1000 V AC/DC
<b>VOLTAGE RANGE</b> DCV: 0...600 V, ± 0,5% ACV: 0...600 V, ± 1,2%
<b>CURRENT RANGE</b> DCA: 0...10A, ± 2,5% ACA: 0...10A, ± 3,0%
<b>RESISTANCE RANGE</b> 0...20 Mohm, ± 0,8%
<b>CAPACITANCE RANGE</b> 0...100 µF, ± 3,0%
<b>FREQUENCY RANGE</b> 0...10MHz, ± 1,5%
<b>DUTY FACTOR RANGE</b> 0,1...99,9 %, ± 1,2%
<b>CONTINUITY TEST</b> Resistance range <1.2 kohm
<b>DIODE TEST</b> 0.3 mA ±10%
<b>PROTECTION CLASS</b> II, double insulation
<b>OVERVOLTAGE CATEGORY</b> CAT III - 1000 V / CAT IV - 600 V Pollution degree 2
<b>LC-DISPLAY</b> up to 4000 (4-segment)
<b>POWER SUPPLY</b> 1x 9 V battery (NEDA 1604, IEC 6F22)
<b>DIMENSIONS</b> 150 x 70 x 48mm
<b>WEIGHT</b> 255g



Large, illuminated display



Easy-to-use function knob



Vibration alarm



### MultiMeter Compact

+ 2 test prods  
+ batteries

**Package size** (W x H x D)  
190 x 315 x 40 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
MultiMeter-Compact	083.034A	4 021563 671236	5