



- Turn on / MEAS
- Addition
- Volume / Area
- Reference Point / Delay Measurement
- Staking-out / Unit
- MENU / Equal
- Subtraction
- Angle / Pythagoras
- Save / Record
- Turn Off / Clear Off

Product description

Features:

One-button operation

Delay Measurement

Angle Measurement

Staking-Out

High accuracy: ± 2 mm (0.079 in)

Automatic calculation of Area and Volume

Indirect measurement by Pythagorean Theorem

Single or continuous measurement

Max or Min distance tracking (display value)

Easy addition or subtraction of measurement

Set up front middle, rear or extension benchmark

Selectable metrics (m, in, ft)

Data store or recall function

Data hold or clear function

Digital Bubble Level, Included

Easy targeting with bright laser pointer

Large Color LCD with backlight and multi-line display (5 lines)

Auto correction and error report technology

Buzzer indication

Battery status Indication

IP54 protection (dust & splash proof)

Auto or manual power off function

Multifunction with intelligent calculation

Compact & handy design

CE, ROHS, FCC certified

Specifications:

Measure Range: 0.05 - 70M(0.16 to 230ft)

Accuracy: ± 2 mm (0.079 inch)

Selectable Unit: m, ft, in

Min. Display Unit: 1mm

Laser Class: Class II 635nm

Laser Maximum Output: <1Mw

Max. Data Storage: 100 Units

Angle of Tilt: ± 90 Degree

Max. Storage Unit: 100

Self Calibration: -9mm to +9mm

Auto Backlight OFF: 5S-60S

Auto Laser OFF: 20S-120S

Auto Switch OFF: 100S-300S

Operation temperature: 0~40C(32~104F)

Storage temperature: -20~60C(14~140F)

Storage Humidity: RH85%

Dust & Splash proof: IP54

Power supply: 3x1.2V 800mAh Ni-MH(Included)

Package Contents:

1 x 70M Laser Distance Meter

1 x Portable pouch

1 x Hanging rope

1 x USB Cable

3 x 1.2V 800mAh Ni-MH Battery

1 x User manual

1 x Retail box