

THICKNESS GAUGE

UTG 200

ULTRASONIC THICKNESS GAUGE

Measuring Range	1.2~220mm(Steel)
Accuracy	$\pm(1\%H+0.1)$ mm
Resolution	0.1mm
Sound Velocity Range	1000~9999m/s
Working Frequency	5MHZ
Minimum Limit for Tube Measuring	\varnothing 20*3 mm(Steel)
Auto Calibration to Assure the Accuracy	yes
Data Store/Recall /Delete Function	yes
Sound Velocity Measurement	yes
Low Battery Indication	yes
Auto Power Off	yes
LCD Backlight Display	Yes
Unit Size	80*38*150mm
Standard Quantity Per Carton	12 PCS
Standard Carton Size	51.7*40.5*32 CM
Standard Carton Gross Weight	14.7 KG
Power Supply	3*1.5V AAA Batteries



UTG 300



Measuring Range	1.0~300mm(Steel)
Accuracy	$\pm(1\%H+0.1)$ mm
Resolution	0.01mm
Sound Velocity Range	1000~9999m/s
Working Frequency	5MHZ
Minimum Limit for Tube Measuring	\varnothing 10mm probe : \varnothing 20*3 mm(Steel) \varnothing 6mm probe: \varnothing 12*2 mm (Steel)
Auto Calibration to Assure the Accuracy	yes
Data Store/Recall /Delete Function	yes
Sound Velocity Measurement	yes
Low Battery Indication	yes
Auto Power Off	yes
LCD Backlight Display	Yes
Unit Size	80*38*150mm
Standard Quantity Per Carton	12 PCS
Standard Carton Size	51.7*40.5*32 CM
Standard Carton Gross Weight	15.1 KG
Power Supply	3*1.5V AAA Batteries