

Light Meter

Home > Products > DC/AC Light Meter > Photosynthesis Light Quantum Meter

New Products

NEW

[Multimeter](#)

[Clamp Meter](#)

[Insulation tester](#)

[Earth/ Ground Tester](#)

[Milli / Micro Ohm Meter](#)

[Power Clamp Meter](#)

[Harmonic Clamp Meter](#)

[Flexible Clamp Meter](#)

[Calibrator](#)

[Solar Power Meter](#)

[Battery Impedance
Tester](#)

[EMF Tester](#)

[Anemometer/
Tachometer](#)

[Thermometer](#)

[Infrared Thermometer](#)

[Humidity Temperature
Meter](#)

[Light Meter](#)

[Sound Level/Vibration
Meter](#)



TES-1339P

Photosynthesis Light Quantum Meter

Product Features

- Autoranging 5 steps and conversion to $\mu\text{mole}/\text{m}^2/\text{s}$ (PPFD: Photosynthetic Photon Flux Density).
- Integral illuminance measurement and conversion to $\text{mole}/\text{m}^2/\text{d}$ (Daily light integral).
- Luminous intensity measurement.
- Point - average function.
- Spectral correction factor function. (include LED)
- Time-hold function.
- Dual Display, 4 digit LCD reading.
- Spectral Sensitivity close to CIE photopic Curve.
- Accurate and Instant response.
- Data Hold function.
- Data memory and read function.
- Reference value stored for relative or percentage deviation measurement.

Particle Counter
 CO/ CO₂ Tester
 PH Meter
 Lan Cable Tester
 Power Supply
 Accessories

- Ripple measurement for STRAY + LIGHT function.
- Comparator function.
- Auto power off function.
- Backlight display function.
- Auto datalogging & USB interface.

Display	Dual display 4 digit LCD reading.
Measuring Range	99.99, 999.9, 9999, 99990, 999900 Lux 9.292, 92.92, 929.2, 9292, 92920 fc Autoranging (5 step) (1 fc = 10.76 Lux)
Overrange Display	OL is displayed
Resolution	0.01 Lux, 0.001 fc
Accuracy	±3% rdg ±5dgt (Calibrated to standard incandescent lamp, 2856 K)
CIE photopic f '1	≤6%
Temperature Characteristics	±0.1% /°C
Measuring Rate	Approximately 5 time/sec
Photosensor	Silicon photodiodes
Data Memory Capacity	99 sets. (Direct reading from LCD display)
Data Logger Capacity	40000 sets.
Operating / Storage Conditions	0°C ~ 40°C <80% RH / -10°C ~ 50°C <70%RH
Power Source	6 pcs AAA size Battery
Battery Life (typical)	100 hours
Photosensor Lead Length	150 cm (approx.)
Photosensor Dimensions	92(L) ×60(W) ×29(H)mm
Dimension	150(L) × 72(W) × 35(H)mm
Weight	320g
Accessories	Carrying case, Instruction manual, Battery, CD software, RS232 to USB cable.