



[Enlarge](#)



Registered Design No.: 0311320.4

[Download Manual](#)

SPECIFICATIONS

| Basic Functions | Range | Best Accuracy |
|--|------------------------------|---------------|
| DC Voltage | 200mV/2V/20V/200V/600V | ±(0.8%+1) |
| AC Voltage | 2V/20V/200V/600V | ±(1.2%+5) |
| AC Current | 2A/20A/200A/400A | ±(1.5%+5) |
| Resistance | 200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ | ±(1%+2) |
| Temperature(°C) | -40°C~1000°C | ±(1%+3) |
| Temperature(°F) | -40°F~1832°F | ±(1%+6) |
| Special Functions | | |
| Auto Ranging | ✓ | |
| Diode | ✓ | |
| Continuity Buzzer | ✓ | |
| Max Hold | ✓ | |
| Data Hold | ✓ | |
| Full Icon Display | ✓ | |
| Sleep Mode | ✓ | |
| Low Battery Display | ✓ | |
| Input Impedance for DC Voltage Measurement | Around 10MΩ | |
| Max Display | 1999 | |

GENERAL CHARACTERISTICS

| | |
|------------------------------|--|
| Power | 3V Battery (AAA) x 2 |
| LCD Size | 35.6 x 18mm |
| Product Colour | Red and Grey |
| Product Net Weight | 220g |
| Product Size | 210 x 75.6 x 30mm |
| Standard Accessories | Test Lead, Batteries, English Manual, Point Contact Temperature Probe, Carrying Bag |
| Optional Accessories* | Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2) |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 40 pcs |
| Standard Carton Measurement | 485 x 415 x 290 mm (0.058 CBM Per Standard Carton) |
| Standard Carton Gross Weight | 15kg |

*Available at Extra Cost
Specifications and other information are subject to change without further notice.

[Back to main menu](#)