

DIGITAL MULTIMETER MS8360F / MS8360G



Specifications

MS8360F MS8360G

Specifications	Range	Accuracy	
DC Voltage	400mV/4V/40V/400V	±(0.5%+2)	±(0.5%+3)
	600V	±(0.8%+2)	±(0.8%+3)
AC Voltage	400mV	±(1.2%+20)	±(2.0%+3)
	4V/40V/400V	±(0.8%+3)	±(0.8%+3)
DC Current	400µA/4000µA/40mA/400mA	±(1.0%+5)	±(0.8%+2)
	1A/10A	±(1.5%+8)	
AC Current	4A/10A		±(1.2%+2)
	400µA/4000µA/40mA/400mA	±(1.0%+8)	±(1.5%+2)
Resistance	1A/10A	±(2.0%+10)	
	400Ω		±(2.0%+2)
Capacitance	4kΩ/40kΩ/400kΩ/4MΩ		±(0.8%+3)
	400Ω/4kΩ/40kΩ/400kΩ/4MΩ	±(1.0%+3)	
Frequency	40MΩ	±(1.2%+15)	±(1.0%+2)
	40nF/400nF/4µF/200µF	±(4.0%+15)	
Duty Cycle	40/400nF/4/40/400/4000µF		±(3.0%+5)
	9.999/99.99/999.9Hz/9.999/99.99/999.9kHz/9.999MHz	±(4.0%+15)	±(0.5%+2)
Temperature	1%~99%	±(2.0%+2)	±(2.0%+2)
	-20°C~0°C		±(5.0%+4)
	1°C~400°C		±(1.0%+3)
	401°C~1000°C		±(2.0%+2)

Features

Display	counts	4000	4000
Auto Ranging	Auto and Manual	●	●
APO	Auto Power Off	●	●
REL	Relative Measurement	●	●
NCV	Non-Contact Voltage Detector	●	●
Transistor hFE	0~1000	●	●
Diode	2.7V	●	●
Continuity Buzzer	<60Ω	●	●
MAX/MIN			●
Bar Graph			●
Data Hold		●	●
Display Backlight		●	●
LBD	Low Battery Display	●	●

General

Power Supply	1×9V6F22 Battery
Product Size	188mm×92mm×50mm/7.4"×3.6"×2.0"
Product Weight	380g/0.83lb
Safety Rating	CE ETL CAT III 600V RoHS

● Feature Difference



MS8360F

VOLTAGE AC 600V
DC 600V

CURRENT AC 10A
DC 10A



MS8360G

VOLTAGE AC 600V
DC 600V

CURRENT AC 10A
DC 10A

